



4700 Broadmoor SE, Suite 200
Kentwood, MI 49512

Telephone: 616-656-7401
Facsimile: 616-656-2022
www.intertek-etlsemko.com

EMECO
Date: March 25, 2015

Report No.:102062025GRR-001
Page 1 of 13

Test Report For:
EMECO
ANSI/BIFMA X5.1-2011
CHAIR TEST STANDARD
18" SU Stool



Intertek



Intertek



Intertek



Intertek



Intertek



Intertek



Intertek



Lynwood Pearson
Project Manager

Anthony Serge
Reviewer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Attention: Magnus Breitling
Emeco
805 Elm Avenue
Hanover, PA 17731
Phone: (717) 637-5951 ext. x4
Fax: (717) 633-6018
Email: magnus@emeco.net

DATE RECEIVED: 3/17/2015
DATES TESTED: 3/19/2015 – 3/24/2015

DESCRIPTION OF SAMPLES:

Part Description: 18" SU Stool
Condition of Test Sample: New

WORK REQUESTED/APPLICABLE DOCUMENTS:

To test the submitted sample per ANSI/BIFMA X5.1-2011 Chair Test Standard for the following test program:

<u>Test No.</u>	<u>Test Description</u>
8	Drop-Dynamic
11	Seating Durability
12	Stability
18	Leg Strength

CONCLUSION:

Test	Results	Notation
ANSI/BIFMA 5.1-2011 #8 Drop Test	Compliant	No loss of serviceability.
ANSI/BIFMA 5.1-2011 #11 Seating Durability	Compliant	No loss of serviceability.
ANSI/BIFMA 5.1-2011 #12 Stability	Compliant	No loss of serviceability.
ANSI/BIFMA 5.1-2011 #18 Leg Strength	Compliant	No loss of serviceability.

TEST EQUIPMENT:

Asset	Description	Cal Date	Cal Due
138272	LOAD CELL 0-1,000 #	10/16/2014	10/16/2015
138039.1	BAG WEIGHT- (300 lbs.)	12/07/2007	VBU
138039.2	BAG WEIGH- (225 lbs.)	12/07/2007	VBU
138042	SEATING IMPACT / 2 STATION	VBU	VBU
138379	STOPWATCH	09/02/2014	09/02/2016
138012	SCALE / 0-1,000 #	11/24/2014	11/24/2015
138148	DIGITAL PROTRACTOR	09/11/2014	09/11/2015
138279	FORCE GAGE; DIGITAL 100LB	03/04/2015	03/04/2016
138916.2	TIMING BOX	VBU	VBU
138112	GRADUATED RULE 36"	10/11/2013	10/11/2018
138170	FRONT STABILITY WEIGHT	04/14/2008	VBU

8. DROP TEST – DYNAMIC:

Date Tested: 3/24/2015
Condition of Test Sample: Production

Test Procedure:

Test Method: ANSI/BIFMA X5.1-2011; Test No. 8
Functional Load: 225 lbs.
Proof Load: 300 lbs.
Drop Height: 6"
Number of Samples Tested: One (1)

Acceptance Criteria:

Functional Load: No structural breakage or loss of serviceability, including stacking ability if applicable.

Proof Load: No sudden and major change in the structural integrity of the product. Loss of serviceability is acceptable.

Results:

Sample ID	Drop Weight	Results
1	Functional Load - 225 lbs.	Pass
	Proof Load - 300 lbs.	Pass

The submitted sample meets the acceptance criteria of the test described above. Refer to the following page for photograph.



DROP TEST – DYNAMIC

11. SEATING IMPACT TEST

Dates Tested: 3/19/2015 – 3/24/2015
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.1-2011; Test No. 11

Section 11.3

Seat Center Impact Test

Bag Diameter: 16"
Bag Weight: 125 lbs.
Number Cycles: 100,000
Height of Drop: 1.2"
Cycles per Minute: 10 to 30

Section 11.4

Load Ease Test

Bag Diameter: 8"
Bag Weight: 165 lbs.
Number of Cycles Required: 20,000 to each Front Corner
Cycles per Minute: 10 to 30
Number of Samples Tested: One (1)

Acceptance Criteria:

There shall be no loss of serviceability to the chair after completion of both the Impact and Load Ease Tests.

Results:

Section 11.3

Sample No.	Number of Cycles	Description of Results
1	100,000	Pass


Section 11.4

Location of Force	Number of Cycles	Description of Results
Left Front Corner	20,000	Pass
Right Front Corner	20,000	Pass

The submitted sample meets the acceptance criteria of the test described above. Refer to the following pages for photographs.



Seating Impact Test



Load Ease Test

12. STABILITY TEST -DYNAMIC (Front and Rear):

Date Tested: 3/25/2015
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.1-2011; Test No. 12
All of the chair's adjustable features shall be set for the most unstable conditions.

Chair Type: III

Weight in Seat

(Rear Stability Only):
Type I: 286 lbs. (13 disks)
Type II: 286 lbs. (13 disks)
Type III: 132 lbs. (6 disks)

Front Stability:

Alternative: N/A
Vertical Load: 135 Lbs.
Horizontal Force: 4.5 Lbs.
Number of Samples Tested: One (1)

Acceptance Criteria:

Front Stability: The chair shall not tip over as the result of the force application of 4.5 lbf..


Rear Stability:

The force to tip shall not be less than:
Type I: Chair must not tip over
Type II: Chair must not tip over
Type III: [F = 1.1 (47 – H) pounds force.]. H is the seat height in inches. For chairs with seat height equal to or greater than 710 mm (28.0 in.), a fixed force of 93 N (20.9 lbf.) shall be applied.

Results:

Sample ID	Front Stability	Rear Stability	Results
1	19.6 lbf. to tip	NA	Pass

The submitted sample meets the acceptance criteria of the test described above. Refer to the following pages for photographs.



Stability Test - Front

18. LEG STRENGTH TEST - FRONT & SIDE APPLICATION:

Date Tested: 3/25/2015
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.1-2011; Test No. 18

Front to Rear Leg Application:

Functional Load: 75 lbf. (Load Each Leg)
Proof Load: 113 lbf. (Load Each Leg)

Side Load Application:

Functional Load: 75 lbf. (Load Each Leg)
Proof Load: 113 lbf. (Load Each Leg)

Number of Samples Tested: One (1)

Acceptance Criteria:

Functional Load: No structural breakage or loss of serviceability, including stacking if applicable.

Proof Load: No sudden and major change in the structural integrity of the product. Loss of serviceability is acceptable.

Results:

Sample ID	Load Application	Functional	Proof	Description of Results
1	Side to Side (Rear Side)	75 lbf.	113 lbf	Pass
	Side to Side (Front Side)	75 lbf.	113 lbf	Pass
	Front to Rear (Left Side)	75 lbf.	113 lbf.	Pass
	Front to Rear (Right Side)	75 lbf.	113 lbf.	Pass

The submitted sample meets the acceptance criteria of the test described above. Refer to the following page for photograph.



LEG STRENGTH TEST

